

Having described preferred embodiments of the invention with reference to the accompanying drawings, it is to be understood that the invention is not limited to those precise embodiments, and that various changes and modifications may be effected therein by one skilled in the art without departing from the scope or spirit of the invention as defined in the appended claims.

1. An accessory for anchoring an article within an enclosure, comprising:

said support element including means for selectively positioning said article at any one selected location of a plurality of widened support expanse locations for disposition of said article in a position in which said article at least partially extends from an article disposition side of said widened support expanse; and

2. The article anchoring accessory according to claim 1, wherein said support element is made in plural joinable sections.

said means for fastening an article includes at least one coupling member carrying a clasping element for engaging said widened support expanse; and

4. The article anchoring accessory according to claim 3, wherein at least one of a structure defining said plurality of perforations and said at least one coupling member includes

means for self-centering said coupling member when effecting engagement thereof with said support element.

5. The article anchoring accessory according to claim 4, wherein:

structure defining at least a portion of said plurality of perforations includes tapered entryways; and

said at least one coupling member includes a tapered structure on a support element engagement end portion of same.

6. The article anchoring accessory according to claim 5, wherein said plurality of perforations are arranged in a bee-hive array of same.

7. The article anchoring accessory according to claim 1, further comprising means for securing said support element to said enclosure.

8. The article anchoring accessory according to claim 7, wherein said securing means includes cooperative securing elements disposable on said bottom of said enclosure and carried on said structure.

9. The article anchoring accessory according to claim 7, wherein said means for securing comprises a gravel layer above said structure.

10. The article anchoring accessory according to claim 1, wherein said support element is adapted for reception proximate a bottom of said enclosure, and includes means for spacing said widened support expanse above said bottom of said enclosure.

11. The article anchoring accessory according to claim 1, wherein said means for securably fastening includes cooperating structural elements carried on each of said article and said widened support expanse.

12. The article anchoring accessory according to claim 1, wherein said means for fastening includes a plurality of projections protruding from said article disposition side of said widened support expanse, said projections comprising male connecting means for cooperating with female connecting means.

13. The article anchoring accessory according to claim 1, wherein:

said widened support expanse includes a plurality of intersecting ribs; and

said plurality of perforations being openings adjoining and defined by ones of said plurality of intersecting ribs.

14. The article anchoring accessory according to claim 1, wherein:

said plurality of widened support expanse locations are arranged in a matrix; and

said support element includes index markings corresponding to intersecting rows and columns of said matrix whereby particular ones of said plurality of perforations can be located by reference to a row and column pair of said index markings.

15. The article anchoring accessory according to claim 1, wherein said widened support expanse includes a plurality of stepped regions.

16. The article anchoring accessory according to claim 15, wherein said support element further includes retaining ledges at the junctions of adjacent ones of said stepped regions.

17. The article anchoring accessory according to claim 1, wherein said support element includes a pair of lateral supports and a plurality of spaced apart rails extending therebetween.

2025 RELEASE UNDER E.O. 14176

18. A method [Method] of anchoring an article within an enclosure, comprising the steps of:

securing a support element within said enclosure;

selectively positioning said article at a one selected location of [a plurality of] locations along said support element for disposition of said article in a position in which said article at least partially extends from an article disposition side of said [widened] support [expanse] element;

fastening said article to said support element at said one selected location[, said means for fastening including] in a manner such that removal of said article from said support element is inhibited by interference between blocking structure carried on the article and cooperating structure carried on the support, said blocking structure and said cooperating structure being movable with respect to [cooperating structure carried on said support element] one another by one of reorientation and deformation of at least one of said blocking structure and said cooperating structure from a position in which said blocking structure interferes with said cooperating structure of said support element and inhibits forcible separation of said article from said support element, to another position in which interference between said blocking structure and said cooperating structure of said support element is at least partially relieved for permitting facilitated detachment of said article from said support element[, said means for fastening being operable from said article disposition side].

19. A kit for anchoring an article within an enclosure, comprising:

25 a support element including structure presenting a wid-  
ened support expanse, receivable within said enclosure  
and being securable with respect thereto, said support  
element being dimensioned such that a periphery  
thereof is proximate an internal peripheral boundary of  
30 said enclosure when received therein, said structure  
defining a plurality of discrete attachment locations  
disposed along said widened support expanse;  
at least one coupling member including means for fas-  
tening said article to said support element at a selected  
35 one of said plurality of discrete attachment locations,  
said means for fastening including blocking structure  
movable with respect to cooperating structure carried  
on said support element by one of reorientation and  
40 deformation of at least one of said blocking structure  
and said cooperating structure from a position in which  
said blocking structure interferes with said cooperating  
structure of said support element and inhibits forcible  
separation of said article from said support element, to  
45 another position in which interference between said  
blocking structure and said cooperating structure of  
said support element is at least partially relieved for  
facilitated detachment of said article from said support  
element, said means for fastening being operable from  
said article disposition side; and  
50 said at least one coupling member including means for  
holding said article in a position in which said article  
extends at least partially from an article disposition side  
of said widened support expanse.

20. A method of anchoring an article within an enclosure, comprising the steps of:

securing a support element within said enclosure;

selectively positioning said article at a one selected location of a plurality of locations along said support element for disposition of said article in a position in which said article at least partially extends from an article disposition side of said [widened] support [expanse] element;

securably fastening said article to said support element at said one selected location for engagement thereto in a manner resisting detachment from said support element[, said means for securably fastening being operable from said article disposition side]; and

said step of securably fastening including providing at least two coupling members each which includes means for engaging said widened support expanse) and each being interconnected by a line, said article being disposed between said article disposition side of said widened support expanse and said line, and said at least two coupling members being securably fastened to said support element.